

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date
26 May 2005 (26.05.2005)

PCT

(10) International Publication Number
WO 2005/047981 A3

(51) International Patent Classification⁷: G03F 7/20

Douglas, C. [US/US]; 1353 Cameo Drive, Campbell, CA 95008 (US). TANAKA, Keiichi [JP/JP]; 7-7-40-1416, Kamiochiae, Chuo-ku, Saitama-ken, Saitama-shi, Saitama 338-0001 (JP).

(21) International Application Number: PCT/US2004/037542

(74) Agent: LEE, Phillip, P.; Beyer Weaver & Thomas, LLP, P.O. Box 70250, Oakland, CA 94612-0250 (US).

(22) International Filing Date: 10 November 2004 (10.11.2004)

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(25) Filing Language: English


(26) Publication Language: English

(30) Priority Data:
60/518,862 10 November 2003 (10.11.2003) US
60/531,129 18 December 2003 (18.12.2003) US

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE,

[Continued on next page]

(54) Title: THERMOPHORETIC TECHNIQUES FOR PROTECTING RETICLES FROM CONTAMINANTS



WO 2005/047981 A3

(57) Abstract: Thermophoresis within lithography systems for protecting reticles from contaminants (e.g., floating particles). Generally, thermophoretic protection is implemented by maintaining the reticle at a higher temperature than its surrounding environment. Thermophoretic protection can be maintained throughout a reticle's use in a lithography system. For example, a reticle can be thermophoretically protected while in storage, through various stages of transportation via a reticle handler (also referred to as an end-effector), to its period of use while attached to a reticle chuck.



SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

- *with international search report*
- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

(88) Date of publication of the international search report:

20 October 2005